

**WHAT IS CLAIMED IS:**

1. A base of a golf club bag, comprising:

5           a main member, which is made of a flexible material, having a bottom portion, a sidewall projected upwardly from a periphery of the bottom portion and at least a flexible portion, such that the bottom portion is divided by the flexible portion into a fixed portion and a movable portion and the sidewall is also divided by the flexible portion into a front portion and a rear portion;

10

          a front supporting device, which is made of a flexible material that harder than the main member, provided in the front portion of the sidewall, and

          a rear supporting device, which is made of a flexible material that harder  
15   than the main member, provided in the rear portion of the sidewall.

          2. The base as defined in claim 1, further comprising at least a middle supporting device, which is made of flexible material that harder than the main member, provided in the rear portion of the sidewall, wherein the rear portion has a  
20   buffer portion respectively between the middle supporting device and the rear supporting device.

          3. The base as defined in claim 1, wherein the flexible portion has a slot on a bottom of the bottom portion.

25

4. The base as defined in claim 1, wherein the flexible portion has two recesses on an interior side of the sidewall.

5. The base as defined in claim 1, further comprising a first connection device fixed to the fixed portion, wherein the first connection device has a plate fixed to the bottom portion and a hook projected from the plate.

6. The base as defined in claim 1, further comprising a second connection device fixed to the rear portion, wherein the second connection device has a hole.

10

7. A base of a golf club bag, comprising:

a main member, which is made of a flexible material, having a bottom portion and a sidewall projected upwardly from a periphery of the bottom portion;

15

a front supporting device, which is made of a flexible material that harder than the main member, provided on an interior side of the front portion of the sidewall, and

20 a rear supporting device, which is made of a flexible material that harder than the main member, provided on an interior side of the rear portion of the sidewall, wherein the front supporting device keep a distance from the rear supporting device and the main member has a flexible portion between the front and the rear supporting devices.

25

8. The base as defined in claim 7, further comprising a middle supporting device fixed on an interior side of the sidewall, wherein the bottom portion the flexible portion between the middle supporting device and the front supporting device and a buffer portion between the middle supporting device and the rear supporting device.

5

9. The base as defined in claim 7, wherein the flexible portion has a slot on a bottom of the bottom portion.

10. The base as defined in claim 7, wherein the flexible portion has two  
10 recesses on the interior side of the sidewall.

11. A base of a golf club bag, comprising:

a main member, which is made of a flexible material, having a bottom  
15 portion, a sidewall projected upwardly from a periphery of the bottom portion and a flexible portion, such that the bottom portion is divided by the flexible portion into a fixed portion and a movable portion and the sidewall is also divided by the flexible portion into a front portion and a rear portion;

20 a supporting device, which is made of a flexible material that harder than the main member, fixed to the sidewall, wherein the supporting device keeps a distance from the flexible portion.

12. The base as defined in claim 11, further comprising a bottom supporting  
25 device, which is made of flexible material that harder than the main member, fixed to

the bottom portion.

13. The base as defined in claim 11, wherein the supporting device is fixed in the sidewall.

5

14. The base as defined in claim 11, further comprising a first connection device fixed to the fixed portion, wherein the first connection device has a plate fixed to the bottom portion and a hook projected from the plate.